



# CARBON DIOXIDE, REFRIGERATED LIQUID

## Safety Data Sheet

### 1. IDENTIFICATION

#### Product identifier

Product Name CARBON DIOXIDE, REFRIGERATED LIQUID

#### Other means of identification

Safety data sheet number LIND-P024  
 UN/ID no. UN2187  
 Synonyms Carbonic Anhydride, Refrigerated Liquid

#### Recommended use of the chemical and restrictions on use

Recommended Use Industrial and professional use.  
 Uses advised against Consumer use

#### Details of the supplier of the safety data sheet

Linde Gas North America LLC - Linde Merchant Production Inc. - Linde LLC  
 575 Mountain Ave.  
 Murray Hill, NJ 07974  
 Phone: 908-464-8100  
[www.lindeus.com](http://www.lindeus.com)

Linde Gas Puerto Rico, Inc.  
 Road 869, Km 1.8  
 Barrio Palmas, Catano, PR 00962  
 Phone: 787-641-7445  
[www.pr.lindegas.com](http://www.pr.lindegas.com)

Linde Canada Limited  
 5860 Chedworth Way  
 Mississauga, Ontario L5R 0A2  
 Phone: 905-501-1700  
[www.lindecana.com](http://www.lindecana.com)

\* May include subsidiaries or affiliate companies/divisions.

For additional product information contact your local customer service.

#### Emergency telephone number

Company Phone Number 800-232-4726 (Linde National Operations Center, US)  
 905-501-0802 (Canada)  
 CHEMTREC: 1-800-424-9300 (North America) +1-703-527-3887 (International)

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Gases under pressure	Refrigerated liquefied gas
Simple asphyxiants	Yes

### Label elements



Signal word

Warning

#### Hazard Statements

Contains refrigerated gas; may cause cryogenic burns or injury  
May displace oxygen and cause rapid suffocation

May increase respiration and heart rate

#### Precautionary Statements - Prevention

Do not handle until all safety precautions have been read and understood  
Use and store only outdoors or in a well ventilated place  
Wear cold insulating gloves, face shield, and eye protection  
Use a backflow preventive device in piping  
Do NOT change or force fit connections  
Close valve after each use and when empty  
Always keep container in upright position

#### Precautionary Statements - Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention/advice.  
IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

#### Hazards not otherwise classified (HNOC)

Not applicable

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Volume %	Chemical Formula
Carbon dioxide	124-38-9	100	CO <sub>2</sub>

## 4. FIRST AID MEASURES

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Skin contact	For dermal contact or suspected frostbite, remove contaminated clothing and flush affected areas with lukewarm water. DO NOT USE HOT WATER. A physician should see the patient promptly if contact with the product has resulted in blistering of the dermal surface or in deep tissue freezing.
Eye contact	If frostbite is suspected, flush eyes with cool water for 15 minutes and obtain immediate medical attention.
Ingestion	Not an expected route of exposure.
Self-protection of the first aider	RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS.

Most important symptoms and effects, both acute and delayed

Symptoms	Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to oxygen-deficient atmosphere (<19.5%) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury or death. Depending on concentration and duration of exposure to carbon dioxide may cause increased respirations, headache, mild narcotic effects, increased blood pressure and pulse, and asphyxiation. Symptoms of overexposure become more apparent when atmospheric oxygen is decreased to 15-17%. Contact with liquid may cause cold burns/frostbite.
----------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
--------------------	------------------------

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific extinguishing methods

Continue to cool fire exposed cylinders until flames are extinguished. Damaged cylinders should be handled only by specialists.

Specific hazards arising from the chemical

Non-flammable gas. Cylinders may rupture under extreme heat.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Monitor oxygen level. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Use personal protection recommended in Section 8.
Other Information	When in contact with refrigerated/cryogenic liquids, many materials become brittle and are likely

to break without warning.

#### Environmental precautions

Environmental precautions Prevent spreading of vapors through sewers, ventilation systems and confined areas.

#### Methods and material for containment and cleaning up

Methods for containment Stop the flow of gas or remove cylinder to outdoor location if this can be done without risk. If leak is in container or container valve, contact the appropriate emergency telephone number in Section 1 or call your closest Linde location.

Methods for cleaning up Return Portable Cryogenic Container to Linde or an authorized distributor.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Never allow any unprotected part of the body to touch uninsulated pipes or vessels that contain cold fluids. The extremely cold metal will cause moist flesh to stick fast and tear when one attempts to withdraw from it. Do NOT change or force fit connections. For applications with moist Carbon Dioxide, 316, 309 and 310 stainless steels may be used as well as Hastelloy® A, B, & C and Monel®. Ferrous nickel alloys are slightly susceptible to corrosion. At normal temperatures carbon dioxide is compatible with most plastics and elastomers.

Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distance, use a cart designed to transport cylinders. Never attempt to lift a cylinder by its valve protection cap. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing leak to occur. Use an adjustable strap wrench to remove over-tight or rusted caps. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Use only with adequate ventilation. Use a backflow preventive device in piping. Close valve after each use and when empty. Ensure the complete gas system has been checked for leaks before use.

Never put cylinders into trunks of cars or unventilated areas of passenger vehicles. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit. Never attempt to refill a compressed gas cylinder without the owner's written consent.

Only experienced and properly instructed persons should handle gases under pressure. Always store and handle compressed gas cylinders in accordance with Compressed Gas Association, pamphlet CGA-P1, Safe Handling of Compressed Gases in Containers. Use only with equipment rated for cylinder pressure.

For additional storage recommendations, consult Compressed Gas Association's Pamphlets P-1, AV-7, G-6, G-6.1, G-6.2, G6.3, G-6.5, G-6.7, G-6.9, PS-5, TB-10, and SB-2.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling. Keep at temperatures below 52°C / 125°F. Full and empty cylinders should be segregated. Use a "first in-first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Stored containers should be periodically checked for general condition and leakage.

Incompatible materials Certain reactive metals, hydrides, moist cesium monoxide, or lithium acetylene carbide diamino may ignite. Passing carbon dioxide over a mixture of sodium peroxide and aluminum or magnesium may explode.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parametersExposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Carbon dioxide 124-38-9	STEL = 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup> (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m <sup>3</sup> (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m <sup>3</sup>	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup> STEL: 30000 ppm STEL: 54000 mg/m <sup>3</sup>

*ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health Immediately Dangerous to Life or Health.*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Local exhaust ventilation to prevent accumulation of high concentrations and maintain air-oxygen levels at or above 19.5%. Oxygen detectors should be used when asphyxiating gases may be released.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). If splashes are likely to occur, wear: Goggles. Face-shield.

Skin and body protection Work gloves and safety shoes are recommended when handling cylinders. Wear cold insulating gloves when handling liquid.

Respiratory protection Use positive pressure airline respirator with escape cylinder or self contained breathing apparatus for oxygen-deficient atmospheres (<19.5%). If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Do not get in eyes, on skin, or on clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Refrigerated liquefied gas
Appearance	Colorless.
Odor	Odorless.
Odor threshold	No information available
pH	No data available
Melting point	No data available
Evaporation rate	Not applicable
Lower flammability limit:	Not applicable
Upper flammability limit:	Not applicable
Flash point	Not applicable
Autoignition temperature	No data available
Decomposition temperature	No data available
Water solubility	Very soluble
Partition coefficient	No data available
Kinematic viscosity	Not applicable

Chemical Name	Molecular weight	Boiling point	Vapor Pressure	Vapor density (air =1)	Gas Density kg/m <sup>3</sup> @20°C	Critical Temperature
Carbon dioxide	44.01	-78.5 °C (Sublimes)	838 psig (5778 kPa) @ 21.1°C	1.522	1.839	31.1 °C

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions

### Chemical stability

Stable under normal conditions.

### Explosion data

Sensitivity to Mechanical Impact    None.  
Sensitivity to Static Discharge        None.

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Due to the presence of Carbon dioxide, Carbonic acid is formed in the presence of moisture.

### Incompatible materials

Certain reactive metals, hydrides, moist cesium monoxide, or lithium acetylene carbide diammino may ignite. Passing carbon dioxide over a mixture of sodium peroxide and aluminum or magnesium may explode.

### Hazardous Decomposition Products

Oxygen. Carbon monoxide (CO).

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation	Acidosis, adrenal cortical exhaustion, and other metabolic stresses have resulted from prolonged continuous exposure to 1-2% carbon dioxide (10,000 ppm-20,000 ppm). The ACGIH TLV of 5,000 ppm is expected to provide a good margin of safety from asphyxiation and undue metabolic stress provided sufficient oxygen levels are maintained in the air. Increased physical activity, duration of exposure, and decreased oxygen content can affect systemic and respiratory effects resulting from exposure to carbon dioxide.
Skin contact	Contact with liquid may cause cold burns/frostbite.
Eye contact	Contact with liquid may cause cold burns/frostbite.
Ingestion	Not an expected route of exposure.

### Information on toxicological effects

Symptoms	Depending on concentration and duration of exposure to carbon dioxide may cause increased respirations, headache, mild narcotic effects, increased blood pressure and pulse, and asphyxiation. Symptoms of overexposure become more apparent when atmospheric oxygen is decreased to 15-17%.
----------	--

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Not classified.
Sensitization	Not classified.
Germ cell mutagenicity	Not classified.

Carcinogenicity	This product does not contain any carcinogens or potential carcinogens listed by OSHA, IARC or NTP.
Reproductive toxicity	Not classified.
STOT - single exposure	Not classified.
STOT - repeated exposure	Not classified.
Chronic toxicity	Chronic harmful effects are not known from repeated inhalation of concentrations below PEL/TLV.
Target Organ Effects	Central Vascular System (CVS), Respiratory system.
Aspiration hazard	Not applicable.

Numerical measures of toxicity

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	Inhalation LC50 (CGA P-20)
Carbon dioxide 124-38-9	-	-	470,000 ppm (Rat)	-

Product Information

Oral LD50

Dermal LD50

No information available.

Inhalation LC50

TCLo - 10,000 ppm (Rat) 24 hours/30 days-continuous

Inhalation LC50

No information available.

**12. ECOLOGICAL INFORMATION**Ecotoxicity

No known acute aquatic toxicity.

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects

Can cause frost damage to vegetation.

Global warming potential (GWP)

1

**13. DISPOSAL CONSIDERATIONS**Waste treatment methods

Disposal of wastes

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to Linde for proper disposal.

**14. TRANSPORT INFORMATION**DOT

UN/ID no.

UN2187

Proper shipping name

Carbon dioxide, refrigerated liquid

Hazard Class

2.2

Special Provisions

T75, TP5

Description

UN2187, Carbon dioxide, refrigerated liquid, 2.2

Emergency Response Guide Number 120

TDG

UN/ID no.

UN2187

Proper shipping name	Carbon dioxide, refrigerated liquid
Hazard Class	2.2
Description	UN2187, Carbon dioxide, refrigerated liquid, 2.2

MEX

UN/ID no.	UN2187
Proper shipping name	Carbon dioxide, refrigerated liquid
Hazard Class	2.3
Description	UN2187, Carbon dioxide, refrigerated liquid, 2.3

IATA

UN/ID no.	UN2187
Proper shipping name	Carbon dioxide, refrigerated liquid
Hazard Class	2.2
ERG Code	2L
Description	UN2187, Carbon dioxide, refrigerated liquid, 2.2

IMDG

UN/ID no.	UN2187
Proper shipping name	Carbon dioxide, refrigerated liquid
Hazard Class	2.2
EmS-No.	F-C, S-V
Description	UN2187, Carbon dioxide, refrigerated liquid, 2.2

ADR

UN/ID no.	UN2187
Proper shipping name	Carbon dioxide, refrigerated liquid
Hazard Class	2.2
Classification code	3A
Tunnel restriction code	(C/E)
Special Provisions	593
Description	UN2187, Carbon dioxide, refrigerated liquid, 2.2, (C/E)

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

US Federal RegulationsSARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	Yes
Reactive Hazard	No



CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Risk and Process Safety Management Programs

This material, as supplied, does not contain any regulated substances with specified thresholds under 40 CFR Part 68. This product does not contain any substances regulated as Highly Hazardous Chemicals pursuant to the 29 CFR Part 1910.110.

US State RegulationsCalifornia Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Carbon dioxide 124-38-9	X	X	X

International Regulations

Chemical Name	Carcinogenicity	Exposure Limits
Carbon dioxide	-	Mexico: TWA= 5000 ppm Mexico: TWA= 9000 mg/m <sup>3</sup> Mexico: STEL= 15000 ppm Mexico: STEL= 27000 mg/m <sup>3</sup>

## 16. OTHER INFORMATION

NFPA

Health hazards 3

Flammability 0

Instability 0

Physical and Chemical  
Properties Simple  
asphyxiant

Note: Ratings were assigned in accordance with Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2009, CGA Recommended Hazard Ratings for Compressed Gases, 3rd Edition.

Issue Date 17-Feb-2015  
Revision Date 17-Feb-2015  
Revision Note Initial Release.

General Disclaimer

For terms and conditions, including limitation of liability, please refer to the purchase agreement in effect between Linde LLC, Linde Merchant Production, Inc. or Linde Gas North America LLC (or any of their affiliates and subsidiaries) and the purchaser.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

End of Safety Data Sheet